

BITUMEN PRIMER

A liquid bitumen solution designed to penetrate and seal porous surfaces, protect bare metal surfaces from corrosion and act as an industrial waterproofing agent.

APPLICATIONS

Automotive Uses: Protects the chassis, undercarriage and inside of wheel arches against stone chipping and corrosion. Suitable for cars, trucks, trailers & caravans.

Industrial Uses: Corrosion preventative coating for steel frames of cars, trailers, ocean going containers. General industrial rust proofing. The high build formula covers weld marks and seams often in one application. Durable steel wire rope coating. Waterproofing agent.

Primer: Penetrates and seals porous surfaces prior to application of bituminous membranes and coatings. Promotes adhesion of bituminous membranes and coatings

APPLICATION INSTRUCTIONS

Directions for use:

Ensure surfaces to be primed are free from oil, dirt, dust and any loose debris. On metal surfaces remove all loose rust with a wire brush. Any areas showing severe corrosion must first be treated with a suitable rust inhibitor or rust converter. Surfaces must be dry for best results, although the product will adhere to damp surfaces.

Application:

Aerosol: Shake can well. Spray surface evenly from a distance of about 15cm. Allow to dry before applying additional coats (if required). After use invert can and spray to clear the nozzle.

Bulk: Apply evenly with a paint brush, roller or airless spray. Avoid pooling. Allow 30 minutes drying time between coats for corrosion protection applications. After use tools can be cleaned with paraffin or white spirits.



HANDLING AND STORAGE

Aerosol: CAUTION: Danger - Extremely flammable aerosol. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat / sparks / flames / hot surfaces. No Smoking. Do not pierce or burn, even when empty. Do not spray onto an open flame or any incandescent material. 75% by mass of the contents are flammable. Avoid contact with skin and eyes. Vapours may cause drowsiness or dizziness. May cause lung damage if swallowed. Limited evidence of a carcinogenic effect. Avoid exposure to vapours, fumes and mists. Use suitable PPE as required. Keep out of reach of children.

Bulk: CAUTION: Harmful – Flammable Liquid and Vapour. Avoid contact with skin and eyes. Vapours may cause drowsiness or dizziness. May cause lung damage if swallowed. Limited evidence of a carcinogenic effect. Avoid exposure to vapours, fumes and mists. Use suitable PPE as required. Keep out of reach of children

PACKAGING

500ml aerosol.

1 litre bulk pack (non-aerosol).

CP/mg/Bitumen Primer – May 2016