



COPPER GASKET SEALER

Spanjaard Copper Gasket Sealer is an adhesive spray used for the positioning of all types of gaskets prior to assembly.

PACKAGING

400ml Aerosol Can.

APPLICATIONS

A gasket positioning spray that becomes tacky approximately 2 minutes after application of the film. The gaskets can be re-aligned for up to one hour. The metallic copper content acts as a filling agent, smoothing out any surface irregularities. A further advantage of the product is that gaskets can be removed and re-used. It must be stressed that the product is intended to be mainly a positioning agent; rounding off the sealing properties of the gasket itself.

Industry: Used on horizontal pipe connections - gasket does not have to be "held" in position as it sticks to surface.

EXAMPLES

All types of gasket material e.g. cork, metal, rubber, composites etc, used in the assembly of diesel and petrol engines as well as pipe flange gaskets, etc.

APPLICATION INSTRUCTIONS

Shake the can before use and spray evenly onto both sides of the gasket. Position gasket. After use the can should be inverted and sprayed to clear the nozzle.

HANDLING AND STORAGE

Extremely flammable aerosol. Pressurised container: Protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat / sparks / flames / hot surfaces. No Smoking. Do not pierce or burn, even when empty. 85% by mass of the contents are flammable. Causes skin and eye irritation. Keep out of reach of children.



CP/mg/Copper Gasket Sealer – May 2016

Certified as an
ISO 9001 Manufacturer
by the SABS

Manufacturers & Distributors of
Special Lubricants & Allied Chemical
Products

SPANJAARD UK LIMITED
2 NEW STREET SQUARE
LONDON
EC4A 3BZ
ENGLAND
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

SPANJAARD LIMITED
PO BOX 7294
JOHANNESBURG
2000
SOUTH AFRICA
TEL: +27 (0)11 386 7100
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

中国区销售和技术服务商：上海昆邦化工有限公司

电话：021-58528856 59923197 传真：021-58528166 E-mail：long@kunbond.com