



ENGINEERING MARKING BLUE

Spanjaard Engineering Marking Blue is a clear dark blue engineering marking dye. It dries rapidly to form a non-flaking, non-glaring water resistant coating.

APPLICATIONS

The fast drying blue liquid or spray is a lay-out ink used for coating onto metal surfaces and then precision scribing on the dried surface with a sharp point.

Spanjaard Engineering Marking Blue can also be used for locating high spots on bearings and other finished metal surfaces.

APPLICATION INSTRUCTIONS

- Ensure good ventilation.
- Ensure metal surface is thoroughly cleaned.
- Spray evenly onto surface from a distance of 20cm.
- Allow to dry and mark as required.
- **Spanjaard Engineering Marking Blue** is easily removed with any petroleum based solvent.

TYPICAL PROPERTIES

Colour	Dark Blue
Density at 20°C, g/ml	1,28

HANDLING AND STORAGE

Store undercover. CAUTION Danger - Extremely flammable aerosol. Pressurised container: Protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat / sparks / flames / hot surfaces. No Smoking. Do not pierce or burn, even when empty. Do not spray onto an open flame or any incandescent material. 98% by mass of the contents are flammable. Causes serious eye irritation. May cause drowsiness or dizziness. Keep out of reach of children.



PACKAGING

300ml Aerosol.
5l Tin

CP/mg/Engineering Marking Blue – May 2016

Certified as an
ISO 9001 Manufacturer
by the SABS

Manufacturers & Distributors of
Special Lubricants & Allied Chemical
Products

SPANJAARD UK LIMITED
2 NEW STREET SQUARE
LONDON
EC4A 3BZ
ENGLAND
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

SPANJAARD LIMITED
PO BOX 7294
JOHANNESBURG
2000
SOUTH AFRICA
TEL: +27 (0)11 386 7100
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

中国区销售和技术服务商：上海昆邦化工有限公司

电话：021-58528856 59923197 传真：021-58528166 E-mail：long@kunbond.com