

FMG & FMG-6 (FOOD MACHINERY GREASE)

A smooth white, economy type food machinery grease. This product is not approved by the US Food & Drug Administration.

APPLICATIONS

Spanjaard FMG should be applied where price is the main consideration and the customer does not need the high grade US FDA approved product - Spanjaard FMG-X.

Spanjaard FMG can be used in medium speed bearing and sleeve applications and resists water wash out and steam cleaning. Protects from rust and oxidation against the action of acidic fruit juices and beverages.

Compatible with most plastics (ABS, GPPS, HIPS, Nylon, Polyacetal, PP and PC).

FMG-6 is a tackier, more adhesive version of the standard **Spanjaard FMG** grease and is available in NLGI Grade 1.5.

APPLICATION INSTRUCTIONS

Apply by hand or grease gun. Do not mix **Spanjaard FMG** with clay-thickened and aluminium complex greases. It is good practice to flush out greases when switching to a new grease. This is achieved by frequent applications of the new grease over a short period.

TYPICAL PROPERTIES

Colour	White
Thickener	Lithium
Drop Point, °C	190
Base Oil	
Viscosity at 40°C, cSt	220
Operating range, °C	-18 to 130
NLGI Grades Worked Pen @ 25C, 1/10mm	
00	415
0	370
1	325
1.5	302
2	280

HANDLING AND STORAGE

Store under cover / indoors with lid closed. Keep out of reach of children.

PACKAGING

NLGI 00,0,1,2 : 500g; 5kg; 15kg; 50kg; 180kg

FMG 6
(NLGI 1.5) : 400g cartridge, 5kg



CP/mg/FMG – Feb 2018

Certified as an
ISO 9001 Manufacturer
by the SABS

Manufacturers & Distributors of
Special Lubricants & Allied Chemical
Products

SPANJAARD UK LIMITED
2 NEW STREET SQUARE
LONDON
EC4A 3BZ
ENGLAND
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

SPANJAARD LIMITED
PO BOX 7294
JOHANNESBURG
2000
SOUTH AFRICA
TEL: +27 (0)11 386 7100
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

中国区销售和技术服务商：上海昆邦化工有限公司

电话：021-58528856 59923197 传真：021-58528166 E-mail：long@kunbond.com