

FMG – X

Spanjaard FMG-X is a premium quality food machinery grease containing polymer additives. It is an odourless, tasteless, water resistant, high performance multi-purpose grease. It is well suited for extreme pressures and higher temperatures.

APPLICATIONS

Spanjaard FMG-X is designed for use in the food processing industry where incidental food contact may occur. All raw materials used in the manufacture of the grease comply with FDA section 21 CFR 178.3570. The grease is registered with the NSF as a category H1 lubricant (Registration No. 141243)

Spanjaard FMG-X is recommended for lubrication in equipment in food and beverage processing plants, including bushes, bearings and other machine parts. Although designed for incidental food contact applications, the excellent lubricating properties allow use in a variety of other applications, allowing rationalisation of lubricants.

Excellent under severe water washing, acid fruit juice contamination, beverage or frequent steam cleaning conditions where it protects against rusting and when the plant is seasonally in-operative under humid conditions.

Spanjaard FMG-X is compatible with most plastics (ABS, GPPS, HIPS, Nylon, Polyacetal, PB and PC, etc.), and the high viscosity base oil and additives provide excellent high corrosive film strength to protect against shock loads.

Anti-wear additives protect against metal-to-metal contact giving longer machine life and greater productivity.

APPLICATION INSTRUCTIONS

Apply by hand or grease gun. Incompatible with all greases except other bentone thickened grease. Flush out old greases completely when switching lubricants. This is achieved by frequent re-greasing over a short time span.

TYPICAL PROPERTIES

NLGI Consistency	1	2
Worked Penetration, 25°C, 1/10mm	325	280

Colour	Off White
Thickener	Bentonite
Working Temperature, °C	-20 to 160
Drop Point, °C	No Drop Point
Rust Test, D1743	Pass
NSF Registration No.	141243 H1

HANDLING AND STORAGE

Store under cover / indoors with lid closed. Keep out of reach of children.



PACKAGING

400ml Aerosol (not NSF approved)
500g; 5kg; 15kg; 50kg; 180kg.

CP/mg/FMG-X – May 2016

Certified as an
ISO 9001 Manufacturer
by the SABS

Manufacturers & Distributors of
Special Lubricants & Allied Chemical
Products

SPANJAARD UK LIMITED
2 NEW STREET SQUARE
LONDON
EC4A 3BZ
ENGLAND
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

SPANJAARD LIMITED
PO BOX 7294
JOHANNESBURG
2000
SOUTH AFRICA
TEL: +27 (0)11 386 7100
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

中国区销售和技术服务商：上海昆邦化工有限公司

电话：021-58528856 59923197 传真：021-58528166 E-mail: long@kunbond.com