



FRICION WINDER LUBRICANT

Spanjaard Friction Winder Lubricant is a specially developed, semi-synthetic, highly adhesive, water repellent friction winder lubricant.

APPLICATIONS

A tacky non-bituminous, semi-synthetic, lubricant specially developed for Friction Winder Ropes in mining and industrial equipment. **Spanjaard Friction Winder Lubricant** penetrates deep into the core of the rope ensuring protection and continued lubrication of the wire strands.

Spanjaard Friction Winder Lubricant contains additives which under boundary conditions ensures that metal to metal contact is minimized and rope life extended.

Spanjaard Friction Winder Lubricant protects against water, backfill plus other contaminants which accelerate deterioration due to rust and wear.

APPLICATION INSTRUCTIONS

Spanjaard Friction Winder Lubricant is a semi-fluid consistency and applied by a brush, drip feed or spray.

TYPICAL PROPERTIES

Density @ 25° C, g/ml	0,86
Colour	Reddish
Texture	Smooth/Tacky
Viscosity, cPs @ 25° C	160

HANDLING AND STORAGE

Prevent ingress of water into product. Use protective handling equipment if continuous contact with the product is envisaged.

PACKAGING

5l, 20l.

CP/mg/Friction Winder Lubricant – May 2016