

## GASKET CLEANER

Spanjaard Gasket Cleaner is a powerful blend of solvents formulated to quickly and easily remove remains of seals and gaskets - it acts by softening the materials making it easy to scrape off. It can also be used to remove industrial coatings (paints and varnishes), adhesives, carbon deposits, baked on oil and grease from metal surfaces. Use of the product eliminates the need for excessive scraping or sanding. It is particularly suitable for removing coatings from aluminum and other soft metals where excessive scraping could damage the surface.

The gel-like consistency, when applied, ensures it remains in the desired location, allowing it to work more effectively.

**Spanjaard Gasket Cleaner is not recommended for use on plastic components.**

**CONTAINS NO METHYLENE CHLORIDE OR n-METHYL PYRROLIDONE.**

### APPLICATION INSTRUCTIONS

**Note:** Spanjaard Gasket Cleaner is highly flammable. Ensure all sources of ignition are removed, and all surfaces to which the product is to be applied are cool, before applying the product.

1. Protect painted surfaces thoroughly from overspray as the product will attack paint.
2. Shake well before use
3. Spray liberally onto the area to be treated
4. Leave for 10 minutes
5. Remove softened material with a scraper or high pressure water jet.
6. Rinse well with water and repeat if necessary.

### TYPICAL PROPERTIES

<b>Appearance</b>	Colourless, opaque gel
<b>Odour</b>	Solvent
<b>Density (of bulk)</b>	1.02 g/ml



### HANDLING AND STORAGE

Extremely flammable aerosol. Pressurised container. protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat / sparks / flames / hot surfaces. No Smoking. Do not pierce or bum, even when empty. Do not spray onto an open flame or any Incandescent material. 90% by mass of the contents are flammable. May cause an allergic skin reaction. Keep out of reach of children. Store indoors.

### PACKAGING

400ml Aerosol

CP/mg/Gasket Cleaner – May 2016