

LIQUID GREASE

A high-quality, semi-fluid, adherent grease containing Molybdenum Disulphide (MoS_2), for penetrating and lubricating chains, linkages and cables. Combines the advantages of a grease with those of a lubricating oil. Applied by aerosol spray.

APPLICATIONS

Spanjaard Liquid Grease is formulated for chains, linkages and cables. It penetrates deep into linkages and adheres to surfaces to give long-lasting protection in inaccessible places under demanding conditions thus dramatically reducing wear (from the MoS_2 present). Product does not drain away like a liquid.

Transport vehicles, uses:-

Cable linkages, springs, control switches, catches, hinges, locks, wheel jacks, seat runners, motorcycle chains, etc.

Industrial uses:-

Wire ropes, winches, pulley blocks, cams, slides, plungers, screw threads, rams, conveyors, rails, rollers, etc.

Domestic uses:-

Hinges, electric garage doors, slides and chains, home workshop equipment, wheel barrows, lawn mowers, etc.

APPLICATION INSTRUCTIONS

Available in aerosol spray form with extension nozzle for pinpointing application into inaccessible places.

TYPICAL PROPERTIES

Colour	Black
Density, 25°C (ASTM D792)	0,9
Viscosity, cSt, 40°C (Brookfield)	1100
Weld Load, kg (ASTM 2596)	250
Operating Temp., °C	-30 to 110

HANDLING AND STORAGE

Extremely flammable aerosol. Pressurised container. protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat / sparks / flames / hot surfaces. No Smoking. Do not pierce or bum, even when empty. Do not spray onto an open flame or any Incandescent material. 70% by mass of the contents are flammable. Use in well ventilated areas. Causes skin irritation. May cause drowsiness or dizziness. Keep out of reach of children. Store under cover.



PACKAGING

400ml Aerosol.

CP/mg/Liquid Grease – Aug 2017