

# QUICKSTART

Instant starting aid with upper cylinder lubricant for all engines when starting is a problem in cold and damp weather. Contains upper cylinder lubricant.

# **APPLICATIONS**

At low temperatures fuel might not vaporise sufficiently giving starting problems.

**Spanjaard Quickstart** is specially formulated to vaporise in cold and damp conditions, giving first time starting.

**Spanjaard Quickstart** can be used for starting all petrol, diesel and paraffin engines in cold and damp weather.

### **REPEATED STARTING ATTEMPTS GIVE**

- Starter motor wear and battery discharge.
- Cylinder flooding and thus reduced chance of starting.
- Oil film wash away by the fuel.
- Fuel dilution of the crankcase oil.

**Spanjaard Quickstart** contains high vapour pressure hydrocarbons to give instant starting and dispersants to deal with any condensed water.

A special upper cylinder lubricant is also included to reduce wear before oil circulation begins.

A special inhibitor gives controlled burning of fuel instead of explosive and damaging pinking.

### APPLICATION INSTRUCTIONS

**Spanjaard Quickstart** can be used on all petrol, diesel and paraffin engines, e.g. trucks, buses, tractors, earth-moving equipment, stationary engines, cars, outboard motors, lawnmowers, locomotives, 2-stroke engines, etc.

**Petrol Engines** - Do not choke or flood carburettor. Spray directly into air-intake for 2-3 seconds while ignition is off and engine is stationary. Start in normal manner. **Diesel and Paraffin Engines** - Check fuel filter for wax blockage that might have crystallized out of the fuel due to sudden cold temperature.

Do not use heater plugs. Spray directly into airintake for 2-3 seconds. Start engine in normal manner.



### HANDLING AND STORAGE

**CAUTION:** Extremely flammable aerosol. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat / sparks / flames / hot surfaces. No Smoking. Do not spray onto an open flame or other ignition sources. Do not pierce or bum, even when empty. 100% by mass of the contents are flammable.

# PACKAGING

350ml aerosol can.

CP/mg/ Quick Start – July 2016

Certified as an ISO 9001 Manufacturer by the SABS Manufacturers & Distributors of Special Lubricants & Allied Chemical Products SPANJAARD UK LIMITED 2 NEW STREET SQUARE LONDON EC4A 3BZ ENGLAND EMAIL: sales@spanjaard.biz WGESTE: www.enapiaard.biz SPANJAARD LIMITED PO BOX 7294 JOHANNESBURG 2000 SOUTH AFRICA TEL: +27 (0)11 386 7100 EMAIL: sales@spanjaard.biz WEBSITE: www.spanjaard.biz

中国区销售和技术服务商:上海昆邦化工有限公司 电话:021-58528856 59923197 传真:021-58528166 E-mail:long@kunbond.com